



## Warnock Hersey Listing Label

 Intertek W/N 04897 DO NOT REMOVE OR COVER THIS LABEL	<b>MODULAR REFRACTORY FIREPLACE</b>	 MADE IN USA Chesapeake, VA 23323 Headquarters Jacksonville, FL 32256
	MAGNUM: <input type="checkbox"/> 28" <input type="checkbox"/> 36" <input type="checkbox"/> 42" <input type="checkbox"/> 48" 82028 82036 82042 82048	
	CERTIFIED TO: UL 127, ULC S610	
	<b>WHI-</b>	
	<b>CLEARANCE TO COMBUSTIBLES:</b>	
	SMOKE DOME FRONT AND ISOKERN CHIMNEY	= 0 in.
	UNIT SIDES AND REAR	= 1.5 in. (38mm)
	COMBUSTIBLE SHEATHING ABOVE OPENING	= 8 in. (203mm)
	TOP SHEATHING OR TRIM TO OPENING SIDES	= 8 in. (203mm)
	MANTEL ABOVE OPENING	= 14 in. (356mm)
	OPENING TO SIDEWALL	= 26 in. (660mm)
	HEARTH EXTENSION BEYOND FRONT	= 20 in. (508mm)
	HEARTH EXTENSION BEYOND SIDES	= 12 in. (305mm)
	COMBUSTIBLE FLOOR (MUST USE FIRE-LITE APPLICATION)	= 4 in. (102mm)
	INSULATION FROM FIREBOX	= 3 in. (76mm)
	USE SOLID WOOD FUEL OR LISTED DECORATIVE GAS VENTED OR UNVENTED APPLIANCE. ALSO FOR USE WITH LISTED METAL CHIMNEY. FIRE-LITE APPLICATION TO USE ECO-STEEL CHIMNEY ONLY.	
	DO NOT USE A FIREPLACE INSERT OR OTHER PRODUCTS NOT SPECIFIED FOR USE WITH THIS PRODUCT. "WARNING" THIS FIREPLACE HAS NOT BEEN TESTED FOR USE WITH GLASS DOORS. TO REDUCE THE RISK OF FIRE OR INJURY, DO NOT INSTALL GLASS DOORS. IF DOORS ARE USED, OPERATE FIREPLACE WITH DOORS FULLY OPEN. WHEN BURNING A DECORATIVE GAS APPLIANCE IN THE FIREPLACE, LOCK THE DAMPER TO THE FULLY OPEN POSITION. DO NOT OPERATE AN UNVENTED GAS LOG SET IN THIS FIREPLACE WITH THE CHIMNEY REMOVED.	
	SEE INSTALLATION AND OPERATING INSTRUCTIONS FOR THIS MODEL AND ICC # ESR-2316,	
	CONTACT BUILDING OFFICIAL PRIOR TO INSTALLATION	
	REFER TO INTERTEK'S DIRECTORY OF BUILDING PRODUCTS FOR DETAILED INFORMATION.	

The latest revision of this manual may be obtained at the Earthcore website:

<https://www.earthcore.com/installation-manuals/>

OR

Scan this QR code



Isokern Fireplace and Chimney Systems are tested and listed to UL standards: UL 127, ULC S610, and UL 103HT. The listing label shown above outlines the listed clearances to combustibles and indicates that the units are suitable for use with solid fuel or listed gas appliances. Refer to the manufacturer's installation manual for detailed description of clearances to combustibles and all other installation information.

A metal listing label similar to those shown above is affixed to each fireplace. Do not remove the listing label from the fireplace.

Prior to beginning installation, contact your local building official to determine the need to obtain a permit.